

STANDARD SEED AND SUPER UNIT

IDEAL FOR AIR SEEDERS OR COMBINES, QUICK UNLOADING & CLEANING

POSTIVELY NO CONTAMINATION, TWO SEPARATE WATERPROOF LIDS



Both 163mm (6 3/8") Augers are hinged to the rear and fitted with over centre catches for ease of transport. Both augers are PVC lined to prevent super build-up. Winches are fitted for raising & lowering of augers. Each bin is fitted with a large sliding trapdoor at the bottom for quick unloading and cleaning. Augers can be run simultaneously or individually. Each waterproof lid is individual operated. Powered by a 13 H/P motor (optional electric start). Simple belt drive, no cross augers or gears to cause problems. Painted interior

SPECIFICATIONS	12' STD	14' STD	14' 6/8	16' STD	18' STD
Chassis width	2.000	2.000	2.000	2.000	2.000
Chassis length	3.600	4.200	4.200	4.800	5.400
Overall height	2.150	2.150	2.150	2.150	2.150
Fill height	1.985	1.985	1.985	1.985	1.985
Bin width	2.400	2.400	2.400	2.400	2.400
Lid opening	1.650	1.950	1.65/2.25	2.250	2.530
Seed capacity	42 bags	49 bags	56/42 bags	56 bags	63 bags
Fertilizer capacity	4.7 tonne	5.5 tonne	4.7/6.3 tonne	6.3 tonne	7.05 tonne
Weight empty	950kg	1010kg	1010kg	1090kg	1200kg
Price (Manual Start Vanguard)	\$.....	\$.....	\$.....	\$.....	\$.....
Price (Electric Start Vanguard)	\$.....	\$.....	\$.....	\$.....	\$.....
Manual start Honda add to the manual start price		\$			
Electric start Honda add to the electric start price		\$			
Hobbs Hoist Stands for lifting bin off of truck to suit all bin sizes		\$.....			

ALL PRICES INCLUDE GST



MANUFACTURED AND DISTRIBUTED BY

40 MOONTA ROAD
KADINA SOUTH AUSTRALIA 5554

Phone 08 8821 1196
Fax 08 8821 2774

Web www.vennings.com.au
Email info@vennings.com.au