

# Vennings PTO Shaft Driven Grain Auger



Illustrated 42' X 9" PTO Drive Auger with optional Jelbart shifter lifter third wheel system with silo winch & new tyres



42' X 9" Fitted with 198cm 78" (closed measurement) PTO Shaft with Safety



PTO Shaft in transport position



Simple Belt Adjustment Standard with 250mm x 3 B Section Heavy Duty Belts



Reversible gear box standard on all Vennings augers. Optional Silo Winch for winching auger into bins Supplied with third wheel system



Safety Cage with removable tow hitch. All exposed flighting is made from 5mm thick plate steel



2000 Lb Heavy Duty Automatic Brake Winch



The manufacturer reserves the right to change specifications without notice or incurring obligation. Information contained herein is from data available at time of printing. Photos for illustration purposes only. All quoted capacities are nominal.





Standard Steel Hopper with safety mesh (emergency stop not fitted to PTO drive augers)



Optional Flexible Hopper with safety mesh



Large 31X10.5R15 6PLY Light Truck Tyres fitted to augers



Document holder attached to hold operating instructions



Optional Drop Spout 5 Section Spout



Optional adjustable discharge spout must be connected to tractor battery

### Optional Jelbart Shifter Lifter Third Wheel System

A basic third wheel system that takes the hard work out of moving augers. The third wheel system can be fitted to the main axle of most A framed augers. By winding a winch the bottom of the auger is lifted and the weight supported on a third



35' X 9" Auger with Jelbart Shifter Lifter fitted in its working position



Jelbart Shifter Lifter in its raised position for road transport



Jelbart Shifter lifter in its working position. The weight is supported on the third wheel



MANUFACTURED AND DISTRIBUTED BY



40 MOONTA ROAD  
KADINA SOUTH AUSTRALIA 5554

Phone 08 8821 1196

Fax 08 8821 2774

Web [www.vennings.com.au](http://www.vennings.com.au)

Email [info@vennings.com.au](mailto:info@vennings.com.au)

The manufacturer reserves the right to change specifications without notice or incurring obligation. Information contained herein is from data available at time of printing. Photos for illustration purposes only. All quoted capacities are nominal.

All Augers are standard with; safety covers, detachable steel hopper, detachable tow hitch, NEW Large 31x10.5R15 6 Ply Heavy Duty Lug Tyres mounted on 6 Stud Sunraysia wheels, 42' to 50' augers fitted with manual automatic brake winch for increased safety, 60' Auger standard fitted with Hydraulic Lift Reversible gearbox in case of Jam and for easy cleanout, 7" auger tube 1.6mm 9" & 10" is 2mm thick for increased strength & durability.

All 9" & 10" augers standard with 5mm thick plate steel large pick up flighting for increased wear & efficiency. Supplied with 198cm (78") (closed measurement) Safety covered PTO Shaft

7" Auger Capable of between 15-18 bags per minute or up to 1 1/2 ton per minute. 9" Auger Capable of between 20-24 bags per minute or up to 2 ton per minute. 10" Auger Capable of between 30-36 bags per minute or up to 2 1/2 ton per minute.

## Standard Equipment

- 198 cm (78") Closed Measurement PTO shaft with safety covers
- Reversible Gearbox in case of jam and for easy cleanout
- New 6 Stud Land Cruiser Hubs and Rims with Large 31X10.5R15 6PLY Light Truck Tyres fitted to augers
- Cast Iron Drive Pulleys
- 250 x 3B Triple Drive Heavy Duty B section Belts
- Detachable Steel Hopper
- Detachable Tow Hitch
- 7" Augers fitted with Heavy Duty Large Pick up Flight
- 9" & 10" Augers fitted with Heavy Duty 5mm Thick Large Pick up Flight
- All moving parts are guarded for your protection and peace of mind
- Heavy Duty undercarriage
- 60' Augers come standard with hydraulic lift (Must be connected to tractor hydraulics)

## Optional Equipment

- Jelbart Shifter Lifter third wheel system comes with Silo Winch for winching auger into bins / silos
- Electric Winch (Must be connected to tractor battery)
- Flexible Plastic Hopper
- Waterproof 7" LCD Monitor and waterproof camera so you can see what's going on at the end of the auger (Must be connected to tractor battery)
- Adjustable 12 volt electric discharge spout (Must be connected to tractor battery)
- Electric Brakes on road wheels
- Mudguards fitted with LED Brake/Turning/Tail lights
- Bean Flighting (reduces capacity on cereals by 2-3 bags per minute)
- Drop Spouts

Size	Approx. Capacity	Approx. Lift
42' X 7"	1 1/2 Ton / Minute	31' 6" (9.60m)
47' X 7"	1 1/2 Ton / Minute	35' (10.67m)
42' X 9"	2 Ton / Minute	30' (9.14m)
50' X 9"	2 Ton / Minute	35' 4" (10.77m)
60' X 9"	2 Ton / Minute	39' 8" (12.09m)
42' X 10"	2 1/2 Ton / Minute	30' (9.14m)
50' X 10"	2 1/2 Ton / Minute	35' 4" (10.77m)
60' X 10"	2 1/2 Ton / Minute	39' 8" (12.09m)



# AUGER PRICES SEPTEMBER 2014

## 7" PTO SHAFT DRIVE AUGERS

Auger Size	Price Including GST
42' X 7"	\$
47' X 7"	\$

## 9" PTO SHAFT DRIVE AUGERS

Auger Size	Price Including GST
42' X 9"	\$
50' X 9"	\$
60' X 9" Standard with Hydraulic Lift	\$

## 10" PTO SHAFT DRIVE AUGERS

Auger Size	Price Including GST
42' X 10"	\$
50' X 10"	\$
60' X 10" Standard with Hydraulic Lift	\$

## OPTIONS TO SUIT PUSH AROUND AUGERS

Electric Winch to Suit 42' & 50'	\$	Jelbart Shifter Lifter Third Wheel System includes Silo Winch			
Electric Brakes on Road Wheels	\$	To Suit 31, 36' & 35' Augers			\$
Mudguards with Brake Tail Turning Lights	\$	To Suit 42, 47' & 50' Augers			\$
Camera Kit Includes Water Proof 7" Colour LCD Screen and one camera near outlet of auger	\$	Bean Flight (Smaller flight will reduce capacity on cereals by 2-3 bags per minute)			
12 Volt Adjustable Spout	\$	Suit 35' X 9"	\$	Suit 35' X 10"	\$
Drop Spout Adaptor	\$	Suit 42' X 9"	\$	Suit 42' X 10"	\$
Drop Spout 3 Section	\$	Suit 50' X 9"	\$	Suit 50' X 10"	\$
Drop Spout 5 Section	\$	<b>ALL PRICES INCLUDE GST</b> But exclude freight & Insurance if applicable			
Drop Spout 7 Section	\$				



Manufactured & Distributed By

40 MOONTA ROAD  
KADINA SOUTH AUSTRALIA 5554  
Phone 08 8821 1196  
Fax 08 8821 2774  
Web [www.vennings.com.au](http://www.vennings.com.au)  
Email [info@vennings.com.au](mailto:info@vennings.com.au)